MATERIAL SAFETY DATA SHEET

HMIS Ratings
Health 2
Flammability 1
Reactivity 0
Protection

1. Product and Company Identification

Material name Dynasolve CU-6

Version # 01

Revision date 01-12-2009
CAS # Mixture
Product code J001

Product use Polyurethane Remover

Manufacturer information Dynaloy, LLC

6445 Olivia Lane

Indianapolis, IN 46226 USA

(317) 788-5694

1-800-424-9300 (CHEMTREC) FOR INTERNATIONAL CALLS

703-527-3887

2. Hazards Identification

Potential health effects

Eyes This product may cause irritation to the eyes. High concentration of product vapors can cause

severe irritation of eyes.

Skin Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.

Inhalation Exposure to oil mist/fume/vapor may cause respiratory tract irritation. Excessive inhalation of this

product may cause headache, dizziness, blurred vision, nausea and vomiting.

Ingestion Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

3. Composition / Information on Ingredients

Components	CAS#	Percent
2-PYRROLIDINONE, 1-METHYL-	872-50-4	40 - 60
2(3H)-FURANONE, DIHYDRO	96-48-0	10 - 30
ETHYLENE GLYCOL PHENYL ETHER	122-99-6	10 - 20
POLY(OXY-1,2-ETHANEDIYL), .ALPHA(NONYLPHENYL)OMEGAHYDR	68412-54-4	2.5 - 10
PROPANOIC ACID, 3-ETHOXY-, ETHYL ESTER	763-69-9	2.5 - 10
PROPANOL, [2-(2-METHOXYMETHYLETHOXY)METHYLETHOXY)-	25498-49-1	2.5 - 10

4. First Aid Measures

First aid procedures

Eye contact Flush immediately with water for at least 15 minutes. Do not rub eyes. If irritation persists get

medical attention.

Skin contact For skin contact flush with large amounts of water while removing contaminated clothing. Wash

contaminated clothing before reuse. If irritation persists, get medical attention.

Inhalation If inhalation of gas/fume/vapor/dust/mist from the material is excessive (air concentration is

greater than the TLV or health effects are noticed), immediately remove the affected person(s) to

fresh air. If symptoms persist, get medical attention.

Ingestion DO NOT induce vomiting unless directed to do so by medical personnel. Call a physician

immediately.

Material name: Dynasolve CU-6 MSDS US

5. Fire Fighting Measures

Extinguishing media

Suitable extinguishing

media

Dry chemical (preferred), alcohol foam, water. Use water to cool fire-exposed containers and to

protect personnel.

Protection of firefighters

Protective equipment and precautions for firefighters

Firefighters should wear full protective clothing including self contained breathing apparatus.

Hazardous combustion

products

Irritating and/or toxic gases may be emitted upon the products decomposition.

6. Accidental Release Measures

Personal precautions Recommendations for personal protective equipment should be followed

Methods for containmentDike the spilled material, where this is possible. Absorb with inert absorbent such as dry clay, sand

or diatomaceous earth, commercial sorbents, or recover using pumps.

Methods for cleaning upAbsorb spill with inert material. Shovel material into appropriate container for disposal.

7. Handling and Storage

Handling As with all chemicals, good industrial hygiene practices should be followed when handling this

material. Avoid getting this material into contact with your skin and eyes.

Storage Keep the container tightly closed and in a cool, well-ventilated place.

8. Exposure Controls / Personal Protection

Engineering controlsUse general ventilation and use local exhaust, where possible, in confined or enclosed spaces.

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Personal protective equipment

Eye / face protection Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection Use impervious gloves. Normal work clothing (long sleeved shirts and long pants) is recommended.

Use of impervious apron and boots are recommended where splashing of the chemical is likely.

Respiratory protection Respiratory protection; not normally required for ambient air concentrations not exceeding the

Occupational Exposure Limit. If ventilation is not sufficient to effectively prevent buildup of vapors,

appropriate NIOSH/MSHA respiratory protection must be provided

9. Physical & Chemical Properties

Physical state Liquid. pH N/AP

Boiling point 410 °F (210 °C) estimated

Flash point 210.2 °F (99 °C) Lowest flashing component

Evaporation rate Not available. **Flammability limits in air,** Not available.

lower, % by volume

Flammability limits in air, upper, % by volume

Chemical stability

Not available.

Stable under normal conditions.

Vapor pressure0.45 hPa estimatedVapor densityNot available.Relative densityNot available.

Solubility (H2O) miscible

Auto-ignition temperature 654.8 °F (346 °C) estimated

Decomposition temperatureNot available.Specific gravity1.0648 estimatedDensity1.0647 g/cm3 estimated

10. Chemical Stability & Reactivity Information

Material name: Dynasolve CU-6 MSDS us

2/4

J001 Version #: 01 Revision date: 01-12-2009 Print date: 01-12-2009

Incompatible materials Strong oxidizing agents (peroxides, chlorine, strong acids).

Hazardous decomposition

products

None known. Irritating and/or toxic fumes and gases may be emitted upon the products

decomposition.

Possibility of hazardous

reactions

Will not occur.

11. Toxicological Information

Toxicological data

Product	Test Results		
Dynasolve CU-6 (Mixture)	Acute Dermal LD50 Rabbit: 14545 mg/kg estimated		
	Acute Oral LD50 Mouse: 4335 mg/kg estimated		
	Acute Oral LD50 Rat: 3478 mg/kg estimated		
	Acute Other LD50 Mouse: 1302 mg/kg estimated		
	Acute Other LD50 Rat: 2133 mg/kg estimated		
Components	Test Results		
ETHYLENE GLYCOL PHENYL ETHER (122-99-6)	Acute Oral LD50 Mouse: 16500 mg/kg		
	Acute Oral LD50 Rat: 1260 mg/kg		
2-PYRROLIDINONE, 1-METHYL- (872-50-4)	Acute Dermal LD50 Rabbit: 8000 mg/kg		
	Acute Oral LD50 Mouse: 5130 mg/kg		
	Acute Oral LD50 Rat: 3914 mg/kg		
	Acute Other LD50 Mouse: 54.5 mg/kg		
	Acute Other LD50 Rat: 80.5 mg/kg		
2(3H)-FURANONE, DIHYDRO (96-48-0)	Acute Oral LD50 Mouse: 1260 mg/kg		
	Acute Oral LD50 Rat: 1540 mg/kg		
	Acute Other LD50 Mouse: 880 mg/kg		

Carcinogenicity

IARC Monographs on Occupational Exposures to Chemical Agents: Overall evaluation

2(3H)-FURANONE, DIHYDRO (96-48-0)

3 Classification not possible from current data.

12. Ecological Information

Ecotoxicological data

Product	Test Results	
Dynasolve CU-6 (Mixture)	LC50 Fish: 1914 mg/l 96 Hours estimated	
Components	Test Results	
ETHYLENE GLYCOL PHENYL ETHER (122-99-6)	LC50 Fathead minnow (Pimephales promelas): 337 - 352 mg/l 96 Hours	

Ecotoxicity No data available for this product. **Environmental effects** No data available for this product.

Persistence and degradability Not available.

13. Disposal Considerations

Disposal instructions Dispose of waste material according to Local, State, Federal, and Provincial Environmental

Regulations.

14. Transport Information

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

15. Regulatory Information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

Material name: Dynasolve CU-6 MSDS US US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

2-PYRROLIDINONE, 1-METHYL- (872-50-4) 1.0 %

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

2-PYRROLIDINONE, 1-METHYL- (872-50-4) Listed.

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

Section 302 extremely hazardous substance

No

Section 311 hazardous

Yes

chemical

State regulations Other state regulations may apply. Check individual state requirements.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

2-PYRROLIDINONE, 1-METHYL- (872-50-4) Listed.

US - California Proposition 65 - CRT: Listed date/Developmental toxin

2-PYRROLIDINONE, 1-METHYL- (872-50-4) Listed: June 15, 2001 Developmental toxin.

US - New Jersey Community RTK (EHS Survey): Reportable threshold

2-PYRROLIDINONE, 1-METHYL- (872-50-4) 500 LBS

US - Pennsylvania RTK - Hazardous Substances: Listed substance

2-PYRROLIDINONE, 1-METHYL- (872-50-4) Listed.

16. Other Information

HMIS® ratings Health: 2

Flammability: 1 Physical hazard: 0

NFPA ratings Health: 2

Flammability: 1 Instability: 0

Disclaimer NOTICE: The information presented herein is based on data considered to be accurate as of the

date of preparation of this Material Safety Data Sheet. However, MSDS may not be used as a commercial specification sheet of manufacturer or seller, and no warranty or representation, expressed or implied, is made as to the accuracy or comprehensiveness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In addition, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from

any hazards inherent in the nature of the product.

Material name: Dynasolve CU-6 MSDS US